

PANEL MOUNT SWITCH SELECTION GUIDE

PUSHBUTTONS

ROCKERS

IM

- Snap-action, audible tactile feedback
- Ø12mm panel cutout
- Sealed to IP67
- NC+NO
- Multiple colors available



IP

- Solid and illuminated
- Tactile feedback
- Variety of terminal options
- Round or square actuator
- Sealed to IP67
- Many color options available
- Momentary or latching function



IB

- Momentary (NO) with tactile feedback
- Snap-in mount
- Tactile feedback
- Sealed to IP54
- Variety of actuator colors
- Solder lug, quick connect or PC terminals



KR

- Solid or illuminated
- Sealed up to IP68
- Laser etched symbols
- Wide choice of color
- Unique rocker design



IS

- Momentary (NO) with tactile feedback
- Threaded bushing
- Tactile feedback
- Sealed to IP67
- Variety of actuator colors
- Solder lug, quick connect or PC terminals



IC

- Momentary (NO) with tactile feedback
- Metal bushing
- Sealed to IP67
- Round or square actuator
- Variety of actuator colors available



IL

- Solid or illuminated
- Ø12mm panel cutout
- Max panel thickness: .393" (10mm)
- Sealed to IP67
- Available with solder lug, PC pins or wire leads
- Reduced bezel option available



KL

- Solid or illuminated
- Single sided locking feature
- Sealed up to IP68
- Laser etched symbols
- Wide choice of color
- Unique rocker design



IZ

- Solid or illuminated
- Ø16mm panel cutout
- Sealed to IP67
- Available in metal and plastic body
- Momentary or latching function



IR

- Solid or illuminated
- Ø16mm panel cutout
- Round or square bezel shape
- Sealed to IP67
- Available with solder lug, PC pins or wire leads
- Momentary or latching function



KG

- Solid or illuminated
- Raised protection bezel
- Sealed to IP65
- Standard symbols available
- Variety of color choices



IQ

- Solid or illuminated
- 16mm cutout
- Snap in mount
- Sealed to IP54
- Momentary or latching
- Round or square bezel shape



IA

- Soft feel, membrane actuator
- Tactile feedback
- Sealed to IP67
- Resistant to dust, sand, water, frost
- Variety of actuator colors



IHL

- Hall effect
- Linear 0.5 to 4.5V output
- Sealed to IP67
- Rated to 5 million cycles
- 3 different force ratings available
- Ø12mm panel cutout



2600

- Solid or illuminated
- 16A 125VAC
- Single or double pole
- 3 rocker shapes
- Peak currents available



13000

- 1/4" threaded bushing
- Single or double pole
- Silver or gold plated contacts
- Quick break momentary
- Several cap colors available



IHS

- Hall effect
- Sealed to IP67
- Momentary (NO)
- Rated to 5 million cycles
- Ø12mm panel cutout



FM

- Solid or illuminated
- 16A 125VAC
- Single or double pole
- Protective boot available



130000 x 778

- High performance
- Threaded bushing
- Double pole, double throw
- Fully sealed to IP67



FP

- 24mm panel cutout
- Momentary or latching function
- Pad printed or laser etched marking available
- Fully backlit legends



300, 400 & 9000

- Threaded bushing selections
- Compact, cylinder shape
- Single pole, single throw NC+NO
- Solder lug or PC terminals



MT

- Single pole, double throw
- Rocker/Toggle function
- Ø17.65mm cutout
- Rated up to 6A 125VAC
- Sealed to IP67



13000 PUSH/PULL

- Unique ergonomic push-pull function
- 24.8mm red anodized aluminum actuator
- O-ring, epoxy sealed
- 4 A 24VDC
- Two poles only



800 & 18000

- Snap action momentary
- 18000 - miniature, to 1A
- Single or double pole
- Solder lug or PC terminal
- Epoxy sealed



1200

- Up to 8A 125VAC
- Momentary NC+NO action
- Single pole
- Plastic or metal plunger
- UL, CSA, VDE



AS

- Snap-in, single pole
- 2 or 3 positions
- Sealed and double insulated
- Solder lug or PC terminals
- Several actuator colors



10400

- Momentary with solder lug terminals
- Single or double pole
- Silver or gold plated contacts
- Optional color caps



8000

- Momentary or alternate action
- Single or double pole
- Long bushing
- Numerous plunger, bushing & accessory options



RP

- Momentary (NO) with tactile feedback
- Sealed to IP67
- Resistant to frost
- 6" and 12" wire leads



7000

- Single or double pole
- Rocker or Paddle style
- Wide variety of actuators
- Actuator and bezel color options



4700 & 4800

- 6A 125VAC
- Alternate action
- Single or double pole
- Full actuator return
- Multiple actuator colors



9400 & 9600

- Momentary, NC, NO or NC/NO
- Two case lengths
- Sealing options
- Several plunger options



S & SR

- Single or double pole
- Rocker or Paddle style
- Silver or gold plated contacts
- Different actuator styles and colors



PANEL MOUNT SWITCH SELECTION GUIDE

TOGGLES

12000X778

- High performance for military applications
- Mil STD 3950
- Mil STD 83731
- 15/32" threaded bushing
- Sealed to IP67
- Double shelled case & pinned lever



3500

- Industrial grade and fully sealed
- 20A 125VAC
- Single or double pole
- 15/32" bushing
- Sealed to IP67
- Variety of lever styles available



5000

- Miniature toggle with 6 bushing options
- 17 different actuator styles
- 1, 2, 3 and 4 pole
- 8 functions including maintained and momentary
- UL, CSA, CECC approved



55000

- VDE approved
- Miniature toggle with 6 bushing options
- 17 different actuator styles
- 8 functions including maintained and momentary
- 1 - 4 pole, with added electrical insulation



ST

- Single or double pole
- Dry circuit through power ratings
- Solder lug or PC terminals
- Silver or gold plating
- Ultra rugged SPDT & DPDT models



600H & 600NH

- 16A 125VAC
- 1, 2 and 3 pole
- 2 and 3 maintained or momentary positions
- Metal or insulated lever
- Locking lever options



11000

- Robust, threaded bushing
- 2 position toggle
- 1, 2, 3 and 4 pole
- Several front panel sealing options
- CECC approved



12000

- Larger 15/32" threaded bushing
- 1, 2, 3 and 4 pole
- DPDT, 3PDT, 4PDT
- Several locking lever options
- Peak current versions available



3600NF

- 6A 250VAC
- Single or double pole
- Fully sealed
- Locking lever options
- UL Listed



1600 & 1700

- Single or double pole
- 4A 125VAC
- Single pole with metal or insulated lever
- 2 & 3 maintained positions
- Variety of actuator styles & colors



6000

- 10A 125VAC
- 1, 2, 3 and 4 pole
- Solder, screw or quick-connect terminals
- Sealing and locking lever options



10600

- Single or double pole
- 2 & 3 positions
- Large, threaded bushing
- Matte black available



4400 & 4600

- 6A 125VAC
- 1, 2 and 3 pole
- High current/voltage rating in a small case
- Metal or insulated lever



ZL

- Single pole
- Ø 4,83 mm threaded bushing
- Silver or gold plated contacts
- Epoxy sealed
- Additional actuator lengths available



MT

- Single pole, double throw
- Rocker / Toggle function
- Ø17,65mm cutout
- Rated up to 6A 125VAC
- Sealed to IP67



1000

- 6A 125VAC
- Single pole, 2 & 3 positions
- Optional insulated levers
- Metal lever & bushing



1500

- 10A 125VAC
- Single pole, 2 & 3 maintained positions
- Insulated lever & bushing
- Variety of actuator styles & colors



OTHER

ANTI VANDAL SWITCHES



PIEZO SWITCHES



EMERGENCY STOPS



INDUSTRIAL CONTROLS



CAPACITIVE SWITCHES



KEYLOCKS



LED INDICATORS



ACCESSORIES



MORE PRODUCTS
AT
www.apem.com



Panel switches

PCB switches

Joysticks

Switch panels

LED indicators